

730



730

Ferrari


PASSION FOR LIFTING

	Lifting Moment	Slewing Angle	Working pressure	Oil tank capacity	Max Oil flow	Max lifting height	Standard crane weight
	tm	°	bar	l	l/min	m	kg
A2	27,4	425	325	180	80	11,90	3105
A3	27,1	425	325	180	80	13,80	3265
A4	26,1	425	325	180	80	15,80	3420
A5	25,6	425	325	180	80	17,90	3560
A6	25,2	425	325	180	80	20,10	3685
A7	24,8	425	325	180	80	22,40	3800
A8	24,3	425	325	180	80	24,70	3900
A6J4	-	425	325	180	80	29,10	4260

Standard

- **Designed in accordance with EN12999+EN13849**
- **Design class: HC1-HD4**
- Load limiting device
- Flanged valves
- Fixed stabilizer cylinders
- Swivel stabilizer foot
- Oil tank
- Radio remote controlled stabilizers (CE)
- EQS Extension Quick System
- SDV Smooth Descent Valve
- Red Power
- P-PB Proportional Power Boost
- P Class - Crane Control System (CE)
- Smart Top monitor 7"- Human Machine Interface (CE)

*) Theoretical lifting capacity
**) Capacity at fixed hook (only if with load limiting device in CE area)



Recommended truck:
G.V.W. ton 19



Via Einstein, 8
42028 Poviglio (RE) Italy
Tel. +39 0522/486308
Fax +39 0522/486330
info@fliferrari.it
marketing@fliferrari.it
www.fliferrari.com



Quality and environmental
certified

Uyghar

Merkez:
19 Mayıs Mah. Sımer. Sümer Sk. Zitaş İş Merkezi D2 Blok D:2 Kozyatağı
Kadıköy - İstanbul

İzmir Ofis:
Manas Bulvarı Folkart Towers Bayraklı İzmir
GSM/WhatsApp: +90 (532) 435 79 81
Faks: +90 (216) 232 23 79
www.uyanhidromaksan.com - info@uyanhidromaksan.com

Data, descriptions, and illustrations pertain only and uniquely to models sold at the time of printing of this brochure. After the date of printing, this information is purely indicative and not binding upon Flli Ferrari. Future modifications are solely at the discretion of Flli Ferrari and are always in compliance with applicable and pertinent safety standards. To obtain updated data, descriptions, and illustrations, contact the manufacturer or your reseller. Cranes manufactured and/or marketed by Flli Ferrari.